

		1717 Doolittle Dr. San Leandro, CA 94577, USA Phone: 1-510-483-7370 FAX: 1-510-483-7371		Energy Recovery, Inc. Technical Specifications Sheet			REV	BY	CKD	REVISION	DATE
				0	AGR	AA	Initial Release	4/29/2025			
DESCRIPTION: TECHNICAL DATA SHEET ATMP-1500-12 PUMP				SHEET							
				1 of 1							
				Document Number							
80942-01			MANUFACTURER								
ERI											
1. Part Number		92380-12		2. Service:			3. Reference:				
OPERATING DATA	4	Liquid	Seawater	33	MATERIALS	Shaft Seal Housing	SAF 2507 Super Duplex SS				
	5	Specific Gravity	1.03	34		Bell Housing	Epoxy Coated GG25 Cast Iron				
	6	Viscosity	1.060 cP @ 70°F (21.1°C)	35		Impeller	EN 1.4539; SAE 904 L; UNS N08904				
	7	Operating Temperature	32°F - 104°F (0°C - 40°C)	36		Impeller Bushing	EN 1.4539; SAE 904 L; UNS N08904				
	8	Minimum Flow	See ERI Document [curve doc]	37		Wear Ring	EN 1.4539; SAE 904 L; UNS N08904				
	9	Maximum Flow	See ERI Document [curve doc]	38		Integrated Check Valve	EN 1.4539; SAE 904 L; UNS N08904				
	10	Minimum Inlet Pressure	14.5psi (1 bar)	39		Sleeve	EN 1.4462; SAF 2205; Duplex SS				
	11	Maximum Outlet Pressure	1200 psi (83 bar)	40		Shaft	EN 1.4462; SAF 2205; Duplex SS				
	12	NPSH _R	See ERI Document [curve doc]	41		Inlet/Outlet	SAF 2507 Super Duplex SS				
	13	Maximum Design Speed	VFD Operated up to 3550 RPM	42		Elastomeric Seals	NBR (neoprene) Rubber				
	14	Efficiency	See ERI Document [curve doc]	43		Shaft Coupling	EN 1.4462; SAF 2205; Duplex SS				
	15	Pump Power	See ERI Document [curve doc]	44		Coupling Guard	Stainless Steel				
	DESIGN	16	Number of Stages	12		45	MOTOR	Motor Support	Steel with Epoxy Paint		
		17	Inlet Size	6" (DN 150)		46		Fasteners (non wetted)	Stainless Steel (EN 1.4301) - 304 SS		
		18	Outlet Size	6" (DN 150)		47		Frame Size	315L		
19		Inlet Connection	Grooved Pipe	48	Frequency	50/60 Hz - Inverter Duty					
20		Outlet Connection	Grooved Pipe	49	Maximum Rated Power	268 HP (200 kW)					
21		Impeller Diameter	5.9" (150 mm)	50	Type	Horizontal FF-600 C-face IEC, IP54					
22		Minimum Impeller Diameter	N/A	51	Voltage	380-420D/660-725Y					
23		Maximum Impeller Diameter	N/A	52	Phase	3					
24		Seal Lubrication	API Plan 02	53	Manufacturer	Siemens					
25		Shaft Seal	Pressure Balance Mechanical Seal	54	Tropicalization	Optional					
26		Seal Face Materials	Ceramic/Silicon Carbide	55	Paint System	Manufacturer Standard C2					
27		Shaft Seal Manufacturer	Manufacturer's standard	56	TESTING	Case Hydrostatic		1750 psi (120 bar)			
28	Shaft Coupling	Torsionally Flexible	57	Impeller Balance		N/A					
29	Thrust Bearing Housing	SAF 2507 Super Duplex Stainless Steel	58	Motor Test		See Motor TDS					
30	Direction of Rotation	CW facing pump drive end	59	Witness Test		Optional					
31	Casing Split	Radial	60	Material Certs		Optional					
32	Thrust Bearing	Ceramic and Carbon	61	Curve Tolerance		ISO9906:2012 3B					
33	Casing Drain	N/A									
Notes: ERI RESERVES THE RIGHT TO MAKE SPECIFICATION CHANGES AT ANY TIME WITHOUT PRIOR NOTICE.											
PRICE: desalsales@energyrecovery.com				SHIPPING:				DELIVERY:			
MANUFACTURER: Energy Recovery, Inc.				MODEL NO. ATMP-1500-12				WEIGHT: 3,485 lb (1,581 kg)			